

PORCELAIN GLS A60

6W | 500 Lm | 2700K

Decorative, ultra dimmable LED filament light bulb with flicker-free technology and 30,000 hours lifetime. This lamp uses 6 watts of power to produce 500 lumens at a CRI of 90.

Item number: ZIK031/6W27E27P



LAMP

Style	A60 GLS
Socket	E27
Filaments	8 x 38mm
Dimmable	Yes, leading & trailing edge
LED Wattage	6w
Equivalent	40w
Lumen	500 lm
CCT LED Chip	2700K
CRI	90
Glass finish	Porcelain (Matte White)
Warranty	3 years

PERFORMANCE

Lifetime	30,000 hours
Cycles on/off	100,000
Starting time	<0.2 sec
Voltage	220v-240v
Hz	50/60 Hz
In-rush protection	3000V
Power factor	>0.9
Operating temperature	-30°C to +40°C
Energy Efficiency	83,3 lm/W
Energy Class	G (G -> A scale)
Beam Angle	360°

DIMENSIONS

Lamp Weight	Up to 45g
Inner / Outer carton q'ty	10 / 100










NB! This light is for indoor use only and is not suitable for use in sealed fixtures, wet environments or for integral primary optics.




EAN13 CODES

ZIK031/6W27E27P 5060537722252

Our lamps as well as the technologies behind them are subject to continuous improvements. All specification is subject to change without notice. Please refer to our website for the most up to date information.

Brand	Lamps tested	Dimmers Tested	Overall compatibility	Comments
	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> GP Panel NGRX Interface Homeworks QS Inline Dimmer myRoom DIN-rail Power Module (Phase Adaptive) RA2 Select In-Line Dimmer 	Excellent	See Test Report
	GLS A60 6W CANDLE C35 4W G9 3W	<ul style="list-style-type: none"> Full Range 	Excellent	Excellent on both leading and trailing edge
	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	<ul style="list-style-type: none"> Full Range 	Very good	All lamps performed well without any issues. There were no current spikes, so, all are compatible with all of our dimmers
	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	<ul style="list-style-type: none"> V-PRO MJP120 V-PRO MJP300 V-PRO IR V-PRO MULTI-POINT V-COM 100 V-COM 180 	Excellent	Excellent compatibility rating when driven in the recommended quantities. All lamps dimmed in a smooth, progressive fashion without flickering, over an extensive brightness range. The lamps extinguish fully when in the "off state" of our remote capable dimmers
	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> Full Range 	Very Good / Excellent	<p>This lamp performed very well with all dimmers with very few areas of criticism. No static flicker was observed at any output level although a slight shimmer while fading was observed with all dimmers except the WMT. While the profile was generally smooth and continuous there was a slight step around the minimum output level.</p> <p>Smoothness of Dimming Minimum brightness from off: <1% Minimum brightness from max: <1% Audible Noise: No audible noise when tested with any recommended dimmer.</p>
	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> Full Range 		Very good
	GLS A60 6W GLS A60 10W GOLFBALL G45 4W GU10 6W	<ul style="list-style-type: none"> Full Range 	Very good	All the bulbs tested dim very well

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4638$ $y=0.4147$ / $u'=0.2632$ $v'=0.5295$
 CCT=2677K (Duv=0.0012) Dominant WL:Ld =584.0nm Purity=63.7%
 Ratio:R=26.4% G=71.5% B=2.1% Peak WL:Lp=622.5nm FWHM=148.0nm
 Render Index:Ra=91.5
 R1 =91 R2 =95 R3 =98 R4 =92 R5 =91 R6 =95 R7 =92
 R8 =79 R9 =53 R10=88 R11=93 R12=82 R13=92 R14=98 R15=86

Photo Parameters:

Flux = 494.5 lm Eff. : 82.28 lm/W Fe = 1.733 W

Electrical parameters:

V = 240.37 V I = 0.02889 A P = 6.011 W PF = 0.8654

LEVEL:OUT WHITE:ANSI_2700K

Status: Integral T = 500 ms Ip = 6498 (10%)

Model: A60 GLS Porcelain 6W 2700K
 Tester:
 Temperature:25.3Deg
 Manufacturer: Zico Lighting

Number:
 Date:2018-11-30
 Humidity:65.0%
 Remarks: